

Biolor-Lot G 820

material No.		Version	1.2
specification	102676	Revision date	02.01.2002
VA-Nr		Print Date	30.03.04
		Page	1 of 6

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING**Product information**

Trade name	:	Biolor-Lot G 820
Company	:	DeguDent GmbH Postfach 1364 D-63403 Hanau
Telephone	:	+49 (0)6181/59-5767
Telefax	:	+49 (0)6181/59-5879
Emergency telephone number	:	+49 (0)180 / 23 24-555

2. COMPOSITION/INFORMATION ON INGREDIENTS**Information on ingredients / Hazardous components**

• Gold		72,00%	
CAS-No.	7440-57-5	EC-No.	231-165-9
• platinum		2,90%	
CAS-No.	7440-06-4	EC-No.	231-116-1
• Iridium		0,10%	
CAS-No.	7439-88-5	EC-No.	231-095-9
• silver		8,00%	
CAS-No.	7440-22-4	EC-No.	231-131-3
• copper		7,00%	
CAS-No.	7440-50-8	EC-No.	231-159-6
• zinc		10,00%	
CAS-No.	7440-66-6	EC-No.	231-175-3
Symbol(s):	F	R-phrases)	R15, R17

3. HAZARDS IDENTIFICATION

Zinc oxide fumes is released during processing
When melting, soldering and grinding:
Do not breathe Dusts and vapours:.

4. FIRST AID MEASURES**Inhalation**

Dusts and vapours:
Remove to fresh air.

Eye contact

Dusts and vapours:
Rinse thoroughly with plenty of water keeping eyelid open.

Biolor-Lot G 820

material No.		Version	1.2
specification	102676	Revision date	02.01.2002
VA-Nr		Print Date	30.03.04
		Page	2 of 6

If eye irritation persists, consult a specialist.

5. FIRE-FIGHTING MEASURES**Suitable extinguishing media**

all extinguishing substances suitable

Specific hazards during fire fighting

The product itself does not burn.

Special protective equipment for fire-fighters

Employ protective equipment commonly used in the event of fire.

Further information

Adapt fire extinguishing methods to site.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions**

none

Methods for cleaning up

Use mechanical handling equipment.

7. HANDLING AND STORAGE**Handling****Safe handling advice**

Do not breathe dust.

Local ventilation.

No particular measures required if used correctly.

If occurs dust / vapour: Wear personal protective equipment

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Components with workplace control parameters**

- platinum**

CAS-No.	7440-06-4	EC-No.	231-116-1
Control parameters	5 mg/m ³		Time Weighted Average (TWA):(EH40 OES)
	1 mg/m ³		Time Weighted Average (TWA):(EU ELV)

- silver**

CAS-No.	7440-22-4	EC-No.	231-131-3
	0,1 mg/m ³		Time Weighted Average (TWA):(EH40 OES)
	0,1 mg/m ³		Time Weighted Average (TWA):(EU ELV)

- copper**

CAS-No.	7440-50-8	EC-No.	231-159-6
	0,2 mg/m ³		Time Weighted Average (TWA):(EH40 OES)
	Fume		
	1 mg/m ³		Time Weighted Average (TWA):(EH40 OES)

SAFETY DATA SHEET (91/155/EWG)**DeguDent**

A Dentsply International Company

Biolor-Lot G 820

material No.		Version	1.2
specification	102676	Revision date	02.01.2002
VA-Nr		Print Date	30.03.04
		Page	3 of 6

Dust and mist.

OES)

2 mg/m³Short Term Exposure Limit (STEL):(EH40
OES)

Dust and mist.

• **Zinc oxide**

CAS-No. 1314-13-2

EC-No. 215-222-5

Control parameters 5 mg/m³Time Weighted Average (TWA):(EH40
OES)

Fume

10 mg/m³Short Term Exposure Limit (STEL):(EH40
OES)

Fume

Engineering measures

Zinc oxide fumes is released during processing
When melting, soldering and grinding:
Local ventilation.

Personal protective equipment**Respiratory protection**

If workplace exposure limit is exceeded apply Dust mask with P2 particle filter.

Hand protection

No special protective equipment required.

Eye protection

safety glasses with side-shields
If dust occurs: basket-shaped glasses

Skin and body protection

No particular measures required.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.
If there is the possibility of skin/eye contact the indicated hand/eye/body protection should be used.
No eating, drinking, smoking, or snuffing tobacco at work. Wash face and/or hands before break and end of work.
If the limits at the workplace are exceeded and/or larger amounts are released (leakage, spilling, dust) the indicated respiratory protection should be used.
Do not inhale fumes, dust, vapour.

9. PHYSICAL AND CHEMICAL PROPERTIES**Appearance**

Form	solid
Colour	yellow
Odour	odourless

Safety data

Melting point/range	760 - 800 °C
---------------------	--------------

Biolor-Lot G 820

material No.		Version	1.2
specification	102676	Revision date	02.01.2002
VA-Nr		Print Date	30.03.04
		Page	4 of 6

10. STABILITY AND REACTIVITY

Conditions to avoid No restrictions

11. TOXICOLOGICAL INFORMATION

Further information No dangerous reactions are known to occur with correct handling and storage.

12. ECOLOGICAL INFORMATION**Elimination information (persistence and degradability)****Behaviour in environmental compartments****Ecotoxicity effects****Further information on ecology**

Further Information Dusts and water soluble alloy types:
Prevent penetration into soil, stretches of water and drainage systems.

13. DISPOSAL CONSIDERATIONS**Product**

Can be used after re-conditioning.

14. TRANSPORT INFORMATION**Transport/further information**

Not classified as dangerous in the meaning of transport regulations.

15. REGULATORY INFORMATION**labelling according to EEC Directive**

Other data According to Annex VI (9.3), Directive 67/548/EEC hazard labelling is not required.

Biolor-Lot G 820

material No.		Version	1.2
specification	102676	Revision date	02.01.2002
VA-Nr		Print Date	30.03.04
		Page	5 of 6

National legislation

16. OTHER INFORMATION**Further information**

Changes since the last version will be highlighted in the margin. This version replaces all previous versions.

The data presented here correspond to the present state of our knowledge and experience and are intended to describe our product with respect to possible safety demands. We imply with this however no guarantee of properties or description of qualities.

SAFETY DATA SHEET (91/155/EWG)**DeguDent***A Dentsply International Company***Biolor-Lot G 820**

material No.		Version	1.2
specification	102676	Revision date	02.01.2002
VA-Nr		Print Date	30.03.04
		Page	6 of 6