

## Unilot 2

material No.		Version	1.2
specification	102687	Revision date	02.01.2002
VA-Nr		Print Date	30.03.04
		Page	1 of 4

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

## Product information

Trade name	:	Unilot 2
Company	:	DeguDent GmbH Postfach 1364 D-63403 Hanau
Telephone	:	+49 (0)6181/59-5767
Telefax	:	+49 (0)6181/59-5879
Emergency telephone number	:	+49 (0)180 / 23 24-555

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

## Information on ingredients / Hazardous components

• <b>Gold</b>		73,00%	
CAS-No.	7440-57-5	EC-No.	231-165-9
• <b>platinum</b>		0,90%	
CAS-No.	7440-06-4	EC-No.	231-116-1
• <b>Palladium</b>		1,00%	
CAS-No.	7440-05-3	EC-No.	231-115-6
• <b>Iridium</b>		0,10%	
CAS-No.	7439-88-5	EC-No.	231-095-9
• <b>silver</b>		13,00%	
CAS-No.	7440-22-4	EC-No.	231-131-3
• <b>zinc</b>		12,00%	
CAS-No.	7440-66-6	EC-No.	231-175-3
Symbol(s):	F	R-phrases)	R15, R17

## 3. HAZARDS IDENTIFICATION

Zinc oxide fumes is released during processing  
When melting, soldering and grinding:  
Do not breathe Dusts and vapours:.

## 4. FIRST AID MEASURES

## Inhalation

Dusts and vapours:  
Remove to fresh air.

## Eye contact

Dusts and vapours:  
Rinse thoroughly with plenty of water keeping eyelid open.

**Unilot 2**

material No.		Version	1.2
specification	102687	Revision date	02.01.2002
VA-Nr		Print Date	30.03.04
		Page	2 of 4

If eye irritation persists, consult a specialist.

---

**5. FIRE-FIGHTING MEASURES**
**Suitable extinguishing media**

all extinguishing substances suitable

**Specific hazards during fire fighting**

The product itself does not burn.

**Special protective equipment for fire-fighters**

Employ protective equipment commonly used in the event of fire.

**Further information**

Adapt fire extinguishing methods to site.

---

**6. ACCIDENTAL RELEASE MEASURES**
**Personal precautions**

none

**Methods for cleaning up**

Use mechanical handling equipment.

---

**7. HANDLING AND STORAGE**
**Handling****Safe handling advice**

Do not breathe dust.

Local ventilation.

No particular measures required if used correctly.

If occurs dust / vapour: Wear personal protective equipment

---

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**
**Components with workplace control parameters**

- **platinum**

CAS-No.	7440-06-4	EC-No.	231-116-1
Control parameters	5 mg/m <sup>3</sup>		Time Weighted Average (TWA):(EH40 OES)
	1 mg/m <sup>3</sup>		Time Weighted Average (TWA):(EU ELV)

- **silver**

CAS-No.	7440-22-4	EC-No.	231-131-3
Control parameters	0,1 mg/m <sup>3</sup>		Time Weighted Average (TWA):(EH40 OES)
	0,1 mg/m <sup>3</sup>		Time Weighted Average (TWA):(EU ELV)

- **Zinc oxide**

CAS-No.	1314-13-2	EC-No.	215-222-5
Control parameters	5 mg/m <sup>3</sup>		Time Weighted Average (TWA):(EH40 OES)
	Fume		
	10 mg/m <sup>3</sup>		Short Term Exposure Limit (STEL):(EH40

## Unilot 2

material No.		Version	1.2
specification	102687	Revision date	02.01.2002
VA-Nr		Print Date	30.03.04
		Page	3 of 4

OES)

Fume

**Engineering measures**

Zinc oxide fumes is released during processing  
When melting, soldering and grinding:  
Local ventilation.

**Personal protective equipment****Respiratory protection**

If workplace exposure limit is exceeded apply Dust mask with P2 particle filter.

**Hand protection**

No special protective equipment required.

**Eye protection**

safety glasses with side-shields  
If dust occurs: basket-shaped glasses

**Skin and body protection**

No particular measures required.

**Hygiene measures**

Handle in accordance with good industrial hygiene and safety practice.  
If there is the possibility of skin/eye contact the indicated hand/eye/body protection should be used.  
If the limits at the workplace are exceeded and/or larger amounts are released (leakage, spilling, dust) the indicated respiratory protection should be used.  
When using do not eat, drink or smoke. Wash face and/or hands before break and end of work.  
Do not inhale fumes, dust, vapour.

---

**9. PHYSICAL AND CHEMICAL PROPERTIES****Appearance**

Form	solid
Colour	yellow
Odour	odourless

**Safety data**

Melting point/range	700 - 760 °C
Density	14,5 g/cm <sup>3</sup>

---

**10. STABILITY AND REACTIVITY**

Conditions to avoid	No restrictions
---------------------	-----------------

---

**11. TOXICOLOGICAL INFORMATION**

Further information	No dangerous reactions are known to occur with correct handling and storage.
---------------------	--

**Unilot 2**

material No.		Version	<b>1.2</b>
specification	<b>102687</b>	Revision date	<b>02.01.2002</b>
VA-Nr		Print Date	<b>30.03.04</b>
		Page	<b>4 of 4</b>

---

**12. ECOLOGICAL INFORMATION****Elimination information (persistence and degradability)****Behaviour in environmental compartments****Ecotoxicity effects****Further information on ecology**

Further Information                      Dusts and water soluble alloy types:

Prevent penetration into soil, stretches of water and drainage systems.

---

**13. DISPOSAL CONSIDERATIONS****Product**

Can be used after re-conditioning.

---

**14. TRANSPORT INFORMATION****Transport/further information**

Not classified as dangerous in the meaning of transport regulations.

---

**15. REGULATORY INFORMATION****labelling according to EEC Directive**

Other data                                      According to Annex VI (9.3), Directive 67/548/EEC hazard labelling is not required.

**National legislation**

---

**16. OTHER INFORMATION****Further information**

Changes since the last version will be highlighted in the margin. This version replaces all previous versions.

The data presented here correspond to the present state of our knowledge and experience and are intended to describe our product with respect to possible safety demands. We imply with this however no guarantee of properties or description of qualities.